

EVALUATION AND DESIGN OF STRUCTURES SUBJECTED TO IMPULSE LOADING

G.Vinod Kumar, K Srikanth, V. Varalakshmi

Civil Dept, Nagole Institute Of Technology And Science, Hyderabad, Telangana

Abstract

In early years the structural Engineering structures are intended to oppose just for conventional burdens like dead loads, live loads, wind loads, quake loads. Be that as it may, presently a days because of fast advancement in science & technology particularly in material science. The fear monger assaults are expanded quickly. These assaults will indicate drastical consequences for human lives just as structural designing structure. On the off chance that we think again into history the primary realized touchy was dark powder (otherwise called explosive) which was a blend of charcoal, sulfur and saltpeter and consumed brutally.

By the around nineteenth century significant blasts will takes set far and wide. In these the remarkable fear based oppressor assaults are world exchange focus (W.T.C 9/11), Pentagon attack & Alfred P. Murrah building. These assaults will makes the real effect on auxiliary creators to take care about drive load thought while planning a structures. Significantly impact burden is thought about for extraordinary structures like research focuses, military weapon offices building & some significant open organization.

This proposition exhibits the properties of various materials utilized for explosives, figuring of drive load over the structure & dynamic examination of structure in manual strategy and simultaneously with programming too. The structure is intended for without motivation load, with impact load (calculated) & with impact load (chose).

Key words: Impulse load, Pentagon attack, 9/11 attack, Materials of explosive

1. Introduction

A bomb blast inside or around a structure can have cataclysmic effects, harming and obliterating interior or outside segments of the structure. It extinguishes enormous structure,

dividers and entryways/windows and closes down structure administrations. The effect from the impact causes flotsam and jetsam, fire and smoke and thus can bring about damage and passing to inhabitants.

Bomb harm to structures relies upon the sort and design of the structure, material utilized, scope of the found touchy gadget and the charge weight. This segment manages the authentic review of significant structures hit straightforwardly by bomb blast and the blow-back to building sub-frameworks. Contextual investigations are looked over different nations and they are in no way, shape or form total the greatest number of blasts can happen and increasingly more inadvertent blow-back to building sub-frameworks can in future, be accounted for. In the event that a structure isn't planned 'for an impact', a steel edge may be better under sensibly little bomb situations since steel has equivalent limit in strain and pressure and cement has limit just in pressure in at one face and pressure is taken by the support at the other face. One doesn't know in which bearing the impact effects will happen.

On the off chance that a structure is intended for an impact, the solid parts improve. They have progressively mass and all the more damping and vitality retaining limit. In the United States, the state division permits just fortified solid structures in high-chance zones.

1.1 Properties of explosive materials

The primary European notice of black powder was by the thirteenth century researcher and teacher Roger Bacon (1220–1292) who recorded a formula of 75% saltpeter (potassium nitrate), 15% charcoal and 10% sulfur. Charcoal and sulfur work as powers in the powdered blend though saltpeter goes about as an oxidizer. impacting was later shown by the Swedish inven-tor Alfred B. Nobel (1833–1896).


Around a similar time, nitration of cellulose to deliver nitrocellulose (NC otherwise called guncotton) was attempted by various gatherings lastly the innovation of NC was accounted for by Schonbein (Basel) and Bottger (Frankfurt) autonomously in 1846. Further, explosive was concocted by Alfred B. Nobel in 1866.

Trinitrotoluene (TNT) was the most generally utilized customary military dangerous during the twentieth century. Despite the fact that it had been utilized widely in the color business

during late 1800s, it was not received for use as a military dangerous until 1902, when the German armed force utilized it to supplant picric corrosive. Dynamite was first utilized in fighting during the Russo-Japanese War (1904–1905). The US Army started its utilization in 1912. After an affordable procedure was produced for the nitration of toluene, TNT turned into the central mounted guns ammo in World War I (1914–1918). The most profitable property of TNT is that it tends to be securely dissolved and thrown alone or with different explosives as a slurry.

1.1.1 Trinitrotoluene

Trinitrotoluene (TNT) [$\text{CH}_3\text{C}_6\text{H}_2(\text{NO}_2)_3$: Structure (2.1)] is one of the most significant high explosives and it has been the most widely recognized customary military hazardous during the twentieth century. First utilized in the Russo-Japanese war in 1905, it turned into the reason for the majority of the explosives utilized in resulting wars. It is acquired by the nitration of toluene. It is a yellow crystalline strong with am.p. 80.4°C and speed of explosion (VOD) 6700 ms^{-1} at 1.58 g cm^{-3} thickness. It is insoluble in H_2O however breaks up in conc. HNO_3 or H_2SO_4 and is accelerated from their answers on including H_2O . It is non-hygroscopic and breaks down in for all intents and purposes every single natural dissolvable. It is truly steady to warm and on capacity and has discovered wide application as a blasting charge hazardous for shells, bombs and projectiles and so forth either alone or blended with different explosives.



NO_2


Fig 1.0: Trinitrotoluene (TNT)

1.1.2 Tetryl

Trinitrophenylmethylnitramine [$(\text{NO}_2)_3\text{C}_6\text{H}_2\text{N}(\text{CH}_3)\text{NO}_2$: Structure (2.2)], otherwise called tetryl or creation detonating (CE) is made by the nitration of dimethylaniline with the

utilization of huge overabundance of HNO_3 (Sp. gr. 1.40). It is a yellow crystalline strong of m.p. 129°C and VOD 7075 ms^{-1} at 1.53 g cm^{-3} thickness. It is increasingly delicate to inception and discovers use as a groundwork or promoter alongside high explosives so as to encourage explosion of less

touchy high explosives. It is significantly more delicate to mechanical effect than TNT and is utilized in admixture with TNT to expand affectability to commencement of the last mentioned. Tetryl has been a generally utilized dangerous since 1906. It is more dominant than TNT (110 – 130% of TNT). Its sensitivity to effect and contact, especially to rifle shoot, is higher than that of TNT. Contingent upon its thickness, tetryl may detonate or explode with generally fluctuating force and in this way with various warms of blast or explosion.




NO_2

1.1.3 Nitroglycerine [$\text{NO}_3\text{CH}_2\text{CHNO}_3\text{CH}_2\text{NO}_3$]

1.1.3 Nitroglycerine [$\text{NO}_3\text{CH}_2\text{CHNO}_3\text{CH}_2\text{NO}_3$]

It is arranged by responding glycerine with a blend of sulfuric and nitric corrosive under painstakingly controlled conditions. It is a lackluster sleek fluid and it is straightforward in unadulterated structure. It possesses thickness 1.6 g cm^{-3} and VOD 7700 ms^{-1} (determined). It is exceptionally delicate to mechanical stun and grating. NG turned into the premise of present day business impact ing explosives and is considered as the principal high unstable found reasonable for down to earth applications. It is only sometimes utilized alone as a touchy yet utilized broadly in charge structures and dynamites.






Fig 1.2 : Nitroglycerine (NG)

1.1.4 Dynamite

Explosive, the advanced impacting unstable was made by Alfred Nobel in 1867. The first explosive was a blend of 75% NG and 25% kieselguhr (a permeable absor-twisted powder that yielded a dry, considerably less touchy material). Despite the fact that it might contain up to 75% NG, explosive is a fine material. It was observed to be relatively alright for transportation, taking care of and was additionally called Nobel's Safety Powder. Explosive is provided in waxed paper enveloped cartridges about 2.5 cm by width and 20 cm long weighing 224 gm each. Comparative pressing is likewise utilized for other NG-based explosives so the cartridges can be stacked in boreholes without opening.

Nobel created coagulated explosive in 1875 by making a jam from the dissolution of a collodion-type nitro cotton in NG, delivering a more dominant dangerous than the straight explosive and one that demonstrated to be more secure. Later ammonium nitrate was additionally utilized in explosive, which made it even more secure and more affordable to create.

CodalProvisions

From IS 4991-1968

To plan a structure fit for opposing these serious however brief length burdens, individuals and joints are allowed to redirect and strain a lot more prominent than is took into consideration common static burdens.

The occurrence Wave qualities depicted by the pinnacle starting over pressure(P_{so}), the over pressure(P_o) and dynamic weight(q_o).

The term the of positive period of impact is commonly little as contrasted and the regular time of the auxiliary components, henceforth might be treated as a motivation issue.

For any blast the pinnacle weights and time lengths might be found by utilizing cubic scaling laws .

Scaled separation $X = \text{Actual separation}$

$W^{1/3}$

Scaled time $t_o = \text{Actual time}$

$W^{1/3}$

Where" W " is the yield of blast with reference to the proportionate weight estimated in tones

" X " is the scaled distance

" t_o " is the scaled time

Table 1.0:Impulse wave parameters

Distance, m x	Peak side on over pressure ratio P_{so}/P_a	Positive phase duration t_o mili- sec	Duration of equivalent triangular pulse t_d mili- sec	Dynamic pressure ratio q_o/p_a	Peak reflected overpressure ratio p_{ro}/p_a
15	8.00	9.50	5.39	10.667	41.60
18	5.00	11.00	7.18	5.208	22.50
21	3.30	16.38	9.33	2.643	12.94
24	2.40	18.65	11.22	1.532	8.48
27	1.80	20.92	13.30	0.920	5.81

30	1.40	22.92	15.39	0.583	4.20
33	1.20	24.95	16.31	0.439	3.45
36	1.00	26.71	17.94	0.312	2.75
39	0.86	28.22	19.20	0.235	2.28
42	0.76	29.74	20.20	0.186	1.97
45	0.66	31.25	21.60	0.142	1.66
48	0.59	32.26	22.70	0.115	1.46
51	0.53	33.52	23.70	0.093	1.28
54	0.48	34.52	24.70	0.077	1.14
57	0.43	35.53	26.40	0.062	1.01
60	0.40	36.29	26.60	0.054	0.93
63	0.37	37.30	27.80	0.046	0.83
66	0.34	38.05	28.76	0.039	0.77
69	0.32	38.81	29.25	0.035	0.72
72	0.30	39.56	29.87	0.031	0.67
75	0.28	40.32	30.71	0.027	0.62
78	0.26	40.82	31.85	0.023	0.58
81	0.25	41.58	31.92	0.022	0.55
84	0.24	42.34	32.00	0.020	0.53
87	0.23	42.84	32.26	0.018	0.50
90	0.22	43.60	33.39	0.016	0.47
93	0.20	44.35	34.70	0.014	0.43
96	0.19	45.46	35.37	0.013	0.41
99	0.18	45.61	36.22	0.012	0.40

3.0 CASE STUDIES

3.1 The World Trade Center, New York

American Airlines Flight 11 crashes into north tower of World Trade Center

9.03 am (1303 GMT)

United Airlines Flight 175 crashes into south tower of World Trade Center

9.31 am (1331 GMT)

US President George W. Bush calls the crashes an “apparent terrorist attack on our country”

9.40 am (1340 GMT)

American Airlines Flight 77, carrying 64 people from Washington to Los Angeles, crashes into Pentagon. Trading on Wall Street called off.

9.48 am (1348 GMT)

The Capitol and West Wing of the White House are evacuated

9.49 am (1349 GMT)

The Federal Aviation Administration bars aircraft takeoffs across the country. International flights in progress told to land in Canada

9.50 am (1350 GMT)

Two World Trade Center – the South tower – collapses

9.58 am (1358 GMT)

Emergency dispatcher in Pennsylvania receives call from a passenger on United Flight 93, who says: “We are being hijacked, we are being hijacked!”

10 am (1400 GMT)

United Flight 93 crashes 139 kilometres southeast of Pittsburgh

10.29 am (1429 GMT)

One World Trade Center – the North tower – collapses

10–11.30 am (1400–1530 GMT)

Government buildings around the US are evacuated, including the Capitol and the White House. The United Nations closes. The Securities and Exchange Commission closes all US financial markets for the day. New York City mayor Rudolph Giuliani calls for evacuation of Lower Manhattan

11.40 am (1540 GMT)

Second World Trade Center collapses



Fig. 3.2.2. WTC Tower with antenna-collapsed scenario: Tower I (courtesy: FEMA 2002, Washington, D.C.)

4.0 Method of analysis and design

There are two methods to calculate the response of impulsive load. They are

1. Differential method
2. Duhamel's integral

4.1 Differential method

From 5.1.2 it is clear that the first figure is Rectangular impulse second figure is half sine wave impulse and third figure is triangular impulse. In differential method the dynamic problem will have two solutions. one is " x_c " and another solution is x_p . Hence the complete solution dynamic problem is

$$x(t) = x_c + x_p$$

The dynamic loading factor can be found in the following way

$$DLF_{\max} = x(t)_{\max} / x_{\text{static}} = 1 / (1 - \beta^2)$$

4.2. Duhamel's integral

Consider the impulse is equal to $F(t) d\tau$ and it acting on a body of mass m , produces a change in velocity which can be determined from Newton's second law of motion.

$$x(t) = \frac{1}{m} \int_0^t F(\tau) \sin \omega_n(t - \tau) d\tau \dots \dots \dots 5.1$$

Which is known as Duhamel's integral, which represents the total displacement produced by the exciting force $F(t)$ acting on the un damped oscillator.




Fig:4.0:Area of steel reinforcement details in column

Conclusions

- □ In this venture the properties of explosives materials are considered
- □ Totally 3 cases investigations have been mulled over for assurance of impact load they are Pentagon building, World exchange focus 9/11 &Alfred P.Murrah building.
- □ After watching these contextual investigations explosives will shows major drastical significant on human lives just as structural Engineering structures.

- Synopsis will be given to how to play out the elements investigation on the structure
- After investigation and plan of structure with extraordinary case. The impact burden will shows significant impact on the worldwide individuals.(segments, establishments)
- The examination between the typical quality of the section and high quality of the segment demonstrated that the basic drive for high quality segment case is essentially higher. This expansion can be credited to the additional stiffeners.
- The surface of the structure to the immediate impact weight can not be ensured: it can, anyway be intended to oppose the shoot weight by expanding the standoff good ways from the purpose of burst
- For high hazard offices, for example, open structures, business tall structures, Design thought extraordinary occasions(Bomb impact, high speed sway) are significant

References

- _1) Dynamics of structures by Ray clough,& joseph penzien
- 2) Dynamics of structures by AK.Chopra
- 3) Structural elements and seismic plan by S.R.Damodarysamy&S.Kavitha
- 4) Indian impact safe code
- 5) A. Khadid et al. (2007), " Blast stacked hardened plates" Journal of Engineering and Connected Sciences, Vol. 2(2) pp. 456-461.
- 6) Video classes of Structural elements course by Pradipta Banerjee NPTEL

