

MINIMIZING ENERGY CONSUMPTION IN A DISASTER RELIEF NETWORK

Anchana BS, Jeejo Vetharaj J, Adlin Femil S
Assistant Professor
Marthandam College of Engineering and
Technology

ABSTRACT: The absence of correspondence between neighbourhood specialists, medical aid responders, and the populace that are available in a cataclysmic event territory, speaks to basic angles which can bargain alleviation tasks in sparing human lives. During catastrophic events (seismic tremors/tidal waves), the ordinary broadcast communications arrange framework in the influenced region could be harmed or unfunctional. This can genuinely bargain the effectiveness of medical aid tasks. In this paper, we propose a gadget-to-gadget (D2D) based structure which, beginning from some fundamental data, for example, positions and battery level of injured individual's gadgets, could give correspondence from a hazardous situation towards a practical region. This structure, used by a base station situated in an utilitarian region, arranges clients of hazardous situation into bunches of clients and for each group select an entryway. This structure allows additionally, to assess the ideal transmission control for every entryway so as to amplify the vitality effectiveness in the region and to make a multibounce way from the hazardous situation to transfer hub limiting the start to finish delay. The reproductions results show that our proposed methodology beats either arbitrary arrangement task and static strategies task in both power allotment and directing way manifestations.

INTRODUCTION: During the most recent couple of years, genuine catastrophic events, for example, tremors, torrents, floods and tempests, causing enormous scale debacles, for example, decimation of structures and frameworks, have been watched around the world. These have rendered individuals destitute and killed many thousand individuals [1]. For sure, as per Joined Countries Office for Fiasco Hazard Decrease (UNISDR), during the most recent twenty years most of calamities, as far as recurrence percentage is spoken to by floods (43,4%) trailed by storms (28,2%), tremors (7.8%) and different sorts. Be that as it may, they have distinctive effect as far as number of exploited people, which in the most pessimistic scenario (for example seismic tremor) compares to a normal of at any rate thirty thousand passings for each year [1].

In such circumstances, giving powerful and auspicious reaction to medical aid solicitations can spare numerous human lives. The significant test looked by medical aid responders, is the convenient localization of exploited people inside the hazardous situation. For the most part, this is conceivable through the gigantic measure of emergency treatment demands generated over the broadcast communications organize foundation in

the hazardous situation. In any case, factors like i) low accessibility and dependability of system framework, ii) loss of Intensity/Vitality and iii) restricted assets and administrations, could firmly affect broadcast communications arrangement foundation [2], [3]. To be sure, because of tremors/torrents media communications organization foundation could be in part or completely pulverized.

In this viewpoint, as of late various research endeavors and institutionalization exercises, for example, the International Media transmission Association - Media transmission Institutionalization Department (ITU-T) with its Attention Gathering on Disaster Help Framework [4], ETSI Terrestrial Trunked RAdio (TETRA) [5] and the 3GPP with the Closeness Administration (Writing) for basic interchanges [6], have been begun. In parallel some specialized arrangements, which enable influenced individuals to speak with their families, have been structured. For instance, Facebook actuated its Wellbeing Check [7] highlight which empowers individuals to give fast security notices to their family and companion during the disaster. Fascinating are likewise the instances of M-Criticalness [8] and SafeCity [9] which empower clients to live stream reports and continuous places of violations and emergency. Notwithstanding, the vast

majority of the present catastrophe the board frameworks depend on a current system foundation which, as expressed previously, couldn't be completely or mostly accessible after a cataclysmic event.

The dissemination of ground-breaking media gadgets, for example, cell phones and tablets, has developed exponentially in the most recent decade. Specifically, as indicated by the Remote World Exploration Discussion, in 2020 seven trillion of remote gadgets will serve seven billion of individuals [10]. Moreover, as indicated by Cisco gauge, there will be 11.6 billion portable associated gadgets by 2021, including Versatile to-Versatile (M2M) modules, which surpass the universes anticipated populace around then (7.8 billion). To such an extent, there will be a high thickness of gadgets sharing the alarm physical radio assets and producing a colossal measure of information traffic, for example month to month worldwide portable information traffic will be 49 exabytes by 2021 [11]. This is making the requirement for another cell innovation alluded to as 5G [12]. Specifically, one of the most encouraging technologies which is being considered as help for the up and coming 5G design is the worldview of Gadget to-Gadget (D2D) remote correspondence. D2D correspondences in

remote system are named as the immediate correspondence between two gadgets, giving a wide scope of points of interest, for example, offloading of cell information traffic, productive utilization of radio range and higher framework throughput because of short separation interchanges, without the utilization of a prior system foundation [13], [14]. For this reasons, since likewise a disaster situation is portrayed by high thickness of clients and constrained assets due harms to Data and Communication Innovation (ICT) Framework, D2D has been as of late viewed as a key empowering innovation for the creation of Catastrophe Alleviation Systems [15], [16]. Another factor which must be considered into a calamity situation, is the come up short on vitality. Without a doubt the majority of specialized gadgets present in a hazardous situation run on battery and afterward recovery of intensity supply and power sparing or vitality efficient systems, result to be basic viewpoints for calamity alleviation organize. The idea of Remote Vitality Gathering (WEH) draws in extraordinary consideration by look into network. Specifically, because of its ability to change over RF radio sig-nals into vitality, WEH is viewed as promising answer for remote obliged organize [17]–[19]. Furthermore a few Vitality Efficient (EE) setups have been proposed in writing

[20]–[23]. For the best of our insight, the majority of these works just spotlight on creating EE arrangement in the feeling of diminishing the vitality utilization of every client's gadget or in bunches of clients so as to drag out system lifetime. In any case, vitality decrease doesn't fundamental implies that the control is productively utilized for transmissions. Therefore we propose an EE Directing and Grouping technique for a calamity situation where we consider EE as the most extreme proportion between feasible rate and the power devoured for transmissions [24]. Furthermore, this paper gives a potential structure which, beginning from some essential accessible information of hubs in a hazardous situation, for example hubs position and battery level, can give an information way stream to every client toward an utilitarian zone or an assistance demand assortment point.

In a catastrophe circumstance (quakes/tidal waves), the greater part of the correspondence arrange foundations are totally crushed. In these situations, a fast and facilitated reaction must be given so as to improve the proficiency of salvage groups in sparing however much as could reasonably be expected lives. At that point is important to build up determined and dependable correspondence connects among exploited people and medical aid

responders [25]. In addition, since crisis circumstance might be progressing for quite a while, framework ought to need to remain usable for broadened period. During the most recent decades a few specialized arrangements, in view of impromptu systems, MANET's, work systems satellite communications and shrewd systems, have been proposed as legitimate contender for tending to the issue of communications among exploited people and emergency treatment responders in a debacle situations.

ARTEMIS and CodeBlue speak to a portion of the principal master presented answers for triaging of unfortunate casualties and productive country of salvage groups. Albeit the two arrangements depend on the use of sensors sent into the region of intrigue, they embrace various techniques for information assortment and trans-mission. Specifically, for triage information transmission, the first endeavors specialists that travel through a dependable conveyed remote impromptu system [26]. In the subsequent one, information trans-mission is performed through the remote sensor arrange made by sent sensors [27].

A framework dependent on a MANET for triage information transportation is spoken to by the Versatile Specialist Electronic Triage Label Framework. For this

situation, versatile specialists, which store and convey triage data about exploited people, are made. Information transportation is performed through the production of a start to finish association among source and goal, over a MANET arrange made by cell phone [28].

The Strategic Medicinal Coordination Framework (TacMedCS), produced for a military setting application, can catch and show continuously information comparative with losses in the war zone. All things considered loss information is gathered through handheld gadgets. Such information, in conjunction with GPS position of the person in question, is then sent by means of a satellite communication. IEEE 802.11 work correspondences can likewise be set up between the diverse handheld units for their coordinated effort [29].

Another methodology is spoken to by M-Desperation [8] and SafeCity [9]. These applications, in logical inconsistency with the past ones which, just screen exploited people and don't give highlights to effectively find or to speak with them, empower iOS or Android clients to stream live reports of emergencies circumstances (video just as sound) over the phone system to a neighborhood open security noting point. They additionally gives constant situation through GPS or Wi-Fi

unique finger impression to guarantee a fitting assistance.

As of late likewise Facebook enacted its Wellbeing Check highlight to empower individuals to give fast security announcements to their family and companion during the calamity [7].

Albeit every one of these arrangements could be advantageous in help ing emergency treatment tasks we can distinguish two basic angles dependent on their operational way: I) the organization of commits gadgets and repeaters to supply a framework, which may require quite a while [26]–[28], ii) the need of a previous or devoted correspondence foundation which could be not completely accessible or ready to acknowledge the tremendous measure of solicitations. [7]–[9], [26]–[29].

An alternate methodology which could beat these issues, is spoken to by the Deal Electronic Triage Tag (Deal ETT) framework. It makes electronic triage labels (ETTs) and transmit them utilizing remote astute correspondences, without requiring an immediate association between end clients [30]. For sure, it depends on Wrangle which is a quest based information spread system for versatile astute communication conditions, making simple to share content

straightforwardly between irregularly associated cell phones [31].

Artful systems abuse physical vicinity between versatile hubs to empower direct correspondence between them. They commonly abuse specially appointed empowering technologies like WiFi-direct or Bluetooth, and bolster dissemination of messages through multi-bounce spacetime ways, i.e., multi-jump ways that create both over space - as in customary impromptu multi-jump systems - and after some time - by misusing contact openings between hubs that become accessible over the long haul because of their portability [32]. Hubs can store, convey and advance messages; courses from the sender and the goal are construct progressively, making opportunistic systems powerful to interruptions. A first exhibition examination about the utilization of sharp systems in calamity situation has been displayed in [33]. In this work, creators expected the need of correspondence between a hazardous situation, wherein no accessible system frameworks are available, and a sound region where triage information and additionally help solicitation ought to show up. All things considered, crafty correspondences are performed through cell phones of either exploited people or medical aid responders. Reenactments were led so as

to get execution assessment as far as message conveyance proportion, organize overhead and cost per message, as capacity of sharp steering conventions, number of produced demand, pace of solicitation age and their measurements.

An increasingly broad idea of framework less communication organize is spoken to by the D2D worldview. In reality, D2D interchanges were at first proposed as another under-lay worldview for improving the exhibition of Long haul Advancement (LTE) systems. It is characterized as a direct communication between two portable clients without crossing the Base Station (BS) or center system. For the most part correspondences can happen either on cell authorized or unlicensed range and the asset control plane could be either independent or constrained by the BS [13]. At that point, because of its significant level of versatility, as of late D2D worldview has considered a key empowering innovation for the creation of Fiasco Help Systems [15]. One of the primary takes a shot at how misusing D2D correspondence in a debacle situation was introduced in [34]. Here, the creators proposed a novel D2D based informing answer for a catastrophe circumstance. The proposed arrangement comprised of a D2D session, constrained by the BS through unique communicate

signals. Clients for which the got sign quality is under a predefined edge, will utilize D2D correspondence for transmitting their messages to different hubs in their closeness. At that point this messages will be transmitted by these hand-off hubs to BS over the customary system framework. Contrasted and the default Arbitrary Access Channel (RACH) based informing system, this methodology brought about decreasing the vitality utilization for those hubs with terrible channel condition. Undoubtedly, they utilize short range correspondence requiring less vitality than an immediate transmission over cell framework, for which higher power than expected is required so as to overcome the uplink way misfortune. Likewise the likelihood of fruitful transmission is improved.

An open wellbeing system engineering utilizing D2D communication framework was proposed in [35]. For this situation, creators considered a situation in which there is an utilitarian region with a working BS and a hazardous situation where BS is completely harmed and UEs have no radio asset. Notwithstanding, misusing the multijump idea of D2D worldview, clients from hazardous situation can: i) speak with one another; ii) communicate with hubs of the utilitarian territory, which goes about as Transfer

Hubs (RN) towards the practical BS. At that point, a verifiable inclusion is given to a non utilitarian region. Undoubtedly, it is demonstrated that the handing-off framework can build the limit, lessen the transmission control for portable host and expand the framework inclusion territory.

As referenced before, notwithstanding the need of providing inclusion, another basic viewpoint in a calamity situation is identified with the inescapable power utilization of gadget in performing transmission. Consequently, recuperation of intensity suputilize is exceptionally applicable. Considering, in [36] the creators have as of late proposed a D2D-based calamity management engineering including WEH and hub bunching. Creators considered an open wellbeing situation wherein the BS of an utilitarian zone wants to transmit its data to a goal situated into a non-useful territory out of its coverage extend. Because of the physical hindrance among source and goal, the BS chooses a Hand-off Hub (RN) which will help the data transmission by means of D2D communication. For such hand-off helped correspondence, they inferred the ideal situation wherein the transfer hub ought to be situated, so as to ensure the base blackout probability. In that situation they considered a WEH procedure to move vitality from wellbeing

territory to hazardous situation, and guarantee no loss of vitality on both transfer and hubs of the hazardous situation. At last they proposed a technique through which hubs in the hazardous situation self-sorts out themselves in gatherings of bunches so as to lessen the normal vitality utilization in the hazardous situation. In this setting they expected that in each bunch a UE Group Head (UERCH) which goes about as organizer of the group. Each UERCH utilize short range correspondence for D2D intra-bunch transmission and long range correspondence for between group correspondence and WEH transmission. It is chosen with the technique detailed in [15], [37].

SYSTEM MODEL AND PROBLEMS FORMULATION

Detailing From the past Province of Craftsmanship investigation, we can see that Catastrophe Situation condition issues are like the ones identified with a Remote Sensor System (WSN). In a disaster situation, we have a few hubs spreaded in a hazardous situation which need to discuss both with a sheltered zone, so as to need support, and each other so as to trade neighborhood informations.

Be that as it may, debacle situations are more basic to address, in actuality, than WSNs. In fact, beginning from hubs with no from the earlier settled positions, is important to make a system foundations with however much as could reasonably be expected long lifetime length and with high unwavering quality, so as to ensure a decent correspondence among unfortunate casualties and emergency treatment responders. Besides, just as for the WSNs, in a calamity situation the vitality of hubs is a significant perspective to consider. To be sure, a hub with a low vitality dangers to stay disengaged and inaccessible by help responder.

From past works [15], [34]–[37], it is seen that a decent method to spare vitality in that circumstances is to embrace a D2D interchanges between nearest hubs and composes them in bunches. These works proposed vitality productive answers for CH races and group creation, naming as vitality proficient an answer which arrive at the base of vitality utilization. In any case, vitality decrease doesn't essential implies that the power is proficiently utilized for transmissions. Thus we propose a Vitality Productive Steering and Bunching strategy for a catastrophe situation where we consider vitality effectiveness as the most extreme proportion between attainable pace of the

group and the power devoured for transmissions.

Moreover, this paper gives a potential structure which, beginning from some essential accessible data of hubs in a hazardous situation, for example hubs position and battery level, can give an information way stream to every client toward an utilitarian territory or an assistance demand assortment point.




Fig:1 Typical Considered Scenario

As outlined in Fig.1, we consider a fiasco situation wherein a base station has been completely harmed and afterward unfortunate casualties are not ready to impart their status or solicitation help. So as to spare vitality, interestingly with the past works [15], [36], [37], in our situation hubs don't effectively take part in the development on bunch pecking order sending guide messages, however they remain in LISTEN mode so as to get orders from an outside element situated in a practical zone.

Specifically we accept the followings:

- A set of N Client Hardware (UE) are conveyed according to a homogeneous Poisson Point Procedure (PPP) Φ with spatial thickness λ_{ue} over a round hazardous situation of beam R ;
- The vitality levels of UEs are consistently dispersed in a range $[E_{min}; E_{max}]$;
- As in [36] we expect that, through a RN, a BS situated in an utilitarian zone can set up a correspondence in a fiasco territory;
- The clients can actuate a crisis application which grant the outside BS to know their positions and battery level;
- Each hub in the hazardous situation is furnished with a long-extend correspondence framework for CHs and a short range correspondence framework for D2D inside the bunch;
- Each bunch will comprise of I_k hubs and one passage which fills in as CH;
- Each door can convey both in Downlink and Uplink with at least one Entryways (GW) through long range

correspondence in a TDM duplexing mode;

- Each entryway plays out a transmissions among its hubs in a TDM duplexing mode both in Uplink and down-interface through short-extend. This implies there is no intra-bunch impedance;

As stated before, the BS knows positions and energy levels of all nodes in the disaster area and the RN's position. The first task is to perform the gateway selection. The full procedure is summarized in Algorithm1 and described in the sequel. The aim of the algorithm is, to select the minimum number of the gateway which are able to cover as much as possible all the disaster area and, at the same time, to give the possibility to construct paths towards the relay.

Since all nodes have the functionalities to serve as gateway, the BS needs to reduce the list of candidates. A first coarse selection is performed selecting those nodes for which energy is greater than the average,

i.e. $E_n > E_{av}$. This constitutes the set of nodes labeled as G_{cand} . Intuitively this selection constraint promotes the maximum network lifetime. For each node present in G_{cand} , the BS evaluates its

relative distance from RN and sorts them from farthest to closest. After that, a fine selection procedure is performed among nodes of this subset. Starting from the farthest node, indicating with d_{G2G} the maximum communication range at which two GWs are supposed able to communicate, i.e. long-range communication, and with d_{D2D} the maximum of short-range communication used for intra cluster transmissions, for the i -th node in G_{cand} , BS creates other two subsets labeled as $D2D_i$ and $G2G_i$ respectively. The most important is $G2G_i$ since it contains nodes that are in the d_{G2G} range but not in the d_{D2D} range. From those nodes which are in $G2G_i$ set, as indicated in line 9, the BS maintains only nodes for which their distance from the RN is less or equal the distance between the RN and the i -th node itself, labeling this subset as RN_{close} . However, there is the possibility that this subset results empty for two main reason: i) the $G2G_i$ set resulted empty; ii) nodes in $G2G_i$ are not closer to RN than the i -th node itself. This block of instructions results in a set called UPDATE, which is a set of nodes that is not necessary in the successive steps of gateway selection. At the end of the process all the selected GWs are grouped into the G_{sel} set.

Summarizing, the above described procedure provide the possibility to:

- Save energy from all nodes in cluster creation since this operation is performed by BS itself;
- Obtain the sufficient number of gateways able to cover all disaster area;
- Guarantee highest lifetime of the network in the disaster area by selecting GWs from a subset of node with higher energy;
- Construct multi-hop paths towards the RN also for farthest GWs;
- Reduce the number of communications between GWs since not all the candidates are selected;

CONCLUSION

In this article, we highlight the importance of a network infrastructure in a natural disaster. After analyzing ICT related issues which could be faced in this context, we proposed an EE framework for natural disaster scenario management based on D2D communications. In particular, we considered a disaster scenario in which a BS was fully damaged and then victims are not able neither to communicate their status nor request help. Exploiting D2D communications, coverage is provided by another BS located into a functional area.

Through our proposed framework and the usage of a relay in its coverage area, starting from basic informations such as position and battery level on nodes in disaster area, functional BS is able to: i) select sufficient number of gateways to cover all disaster area through the mean of cluster creation, ii) assign the proper level of transmission power to each gateway in order to maximize the energy efficiency of the whole area, iii) construct multi-hop path for guaranteeing the data delivery, both in downlink and uplink, minimizing the end-to-end delay. In this context we defined the energy efficiency as the ratio between achievable rate and the power consumed for transmissions. Simulations were performed in MATLAB in order show how our proposed approach better outperforms respect to random policies assignment and static policies assignment either in power allocation and routing path creations.

REFERENCES

- [1]UNISDR. *United Nations Office for Disaster Risk Reduction, Disaster Statistics*. Accessed: Feb. 2019. [Online]. Available: <https://www.unisdr.org/we/inform/disaster-statistics>
- [2]K. Ali, H. X. Nguyen, Q. T. Vien, and P. Shah, “Disaster management communication networks: Challenges and architecture design,” in *Proc. Pervasive Comput. Commun. Workshops (PerCom Workshops)*, Mar. 2015, pp. 537–542.
- [3]T.-C. Le, Q.-S. Nguyen, D.-L. Nguyen, B.-C. Huynh, and T.-C. Dinh, “Design of public safety network and emergency alarm for smart trade centre,” *EAI Endorsed Trans. Ind. Netw. Intell. Syst.*, vol. 5, no. 15, pp. 1–8, Sep. 2018.
- [4]ITU-T. *Focus Group on Disaster Relief System (FG-DR and NRR) Network Resiliency and Recover*. Accessed: Feb. 2019. [Online]. Available: <https://www.itu.int/en/ITU-T/focusgroups/dnrr/Pages/default.aspx>
- [5]ETSI. *Terrestrial Trunked Radio (TETRA)*. Accessed: Feb. 2019. [Online]. Available: <https://www.etsi.org/technologies/tetra>
- [6]3GPP. *LTE for Critical Communication*. Accessed: Feb. 2019. [Online]. Available: <http://www.3gpp.org/news-events/conferences/1468-lte-for-critical-communications>
- [7](2015). *Safety Check*. Accessed: Feb. 2019. [Online]. Available: <https://www.facebook.com/about/crisisresponse/>
- [8]S. Krishnamoorthy and A. Agrawala, “M-Urgency: A next generation, context-aware public safety application,” in *Proc. 13th Int. Conf. Hum. Comput. Interact. Mobile Devices Services (MobileHCI)*, 2011, pp. 647–652. [Online]. Available: <http://doi.acm.org/10.1145/2037373.2037475>

- [9] *SafeCity Get Live Information from the Society*. Accessed: Feb. 2019. [Online]. Available: <http://safecity.nl/>
- [10] K. David, D. Dixit, and N. Jefferies, “2020 vision,” *IEEE Veh. Technol. Mag.*, vol. 5, no. 3, pp. 22–29, Sep. 2010.
- [11] “Cisco visual networking index: Global mobile data traffic forecast update, 2016–2021,” Cisco, San Jose, CA, USA, White Paper. [Online]. Available: <https://www.cisco.com/c/en/us/solutions/collateral/service-provider/visual-networking-index-vni/mobile-white-paper-cll-520862.html>
- [12] G. Fettweis and S. Alamouti, “5G: Personal mobile Internet beyond what cellular did to telephony,” *IEEE Commun. Mag.*, vol. 52, no. 2, pp. 140–145, Feb. 2014.
- [13] A. Asadi, Q. Wang, and V. Mancuso, “A survey on device-to-device communication in cellular networks,” *IEEE Commun. Surveys Tuts.*, vol. 16, no. 4, pp. 1801–1819, 4th Quart., 2014.
- [14] N.-S. Vo, T. Q. Duong, H. D. Tuan, and A. Kortun, “Optimal video streaming in dense 5G networks with D2D communications,” *IEEE Access*, vol. 6, pp. 209–223, 2018.
- [15] G. Fodor, S. Parkvall, S. Sorrentino, P. Wallentin, Q. Lu, and N. Brahmı, “Device-to-device communications for national security and public safety,” *IEEE Access*, vol. 2, pp. 1510–1520, Dec. 2014.
- [16] Z. Kaleem, N. N. Qadri, T. Q. Duong, and G. K. Karagiannidis, “Energy-efficient device discovery in D2D cellular networks for public safety scenario,” *IEEE Syst. J.*, to be published.
- [17] X. Lu, P. Wang, D. Niyato, D. I. Kim, and Z. Han, “Wireless networks with RF energy harvesting: A contemporary survey,” *IEEE Commun. Surveys Tuts.*, vol. 17, no. 2, pp. 757–789, 2nd Quart., 2015.
- [18] T. X. Doan, T. M. Hoang, T. Q. Duong, and H. Q. Ngo, “Energy harvesting-based D2D communications in the presence of interference and ambient RF sources,” *IEEE Access*, vol. 5, pp. 5224–5234, 2017.
- [19] Y. Liu, L. Wang, S. A. R. Zaidi, M. El-kashlan, and T. Q. Duong, “Secure D2D communication in large-scale cognitive cellular networks: A wireless power transfer model,” *IEEE Trans. Commun.*, vol. 64, no. 1, pp. 329–342, Jan. 2016.
- [20] Z. Sheng, H. D. Tuan, T. Q. Duong, H. V. Poor, and Y. Fang, “Low-latency multiuser two-way wireless relaying for spectral and energy efficiencies,” *IEEE Trans. Signal Process.*, vol. 66, no. 16, pp. 4362–4376, Aug. 2018.
- [21] Z. Sheng, H. D. Tuan, A. A. Nasir, T. Q. Duong, and H. V. Poor, “Power allocation for energy efficiency and secrecy of wireless interference networks,” *IEEE Trans. Wireless Commun.*, vol. 17, no. 6, pp. 3737–3751, Jun. 2018.
- [22] Z. Sheng, H. D. Tuan, T. Q. Duong, and H. V. Poor, “Joint power allocation and beamforming for energy-efficient two-way multi-relay communications,” *IEEE Trans.*

Wireless Commun., vol. 16, no. 10, pp. 6660–6671, Oct. 2017.

- [23] V.-D. Nguyen, T. Q. Duong, H. D. Tuan, O.-S. Shin, and H. V. Poor, “Spectral and energy efficiencies in full-duplex wireless information and power transfer,” *IEEE Trans. Commun.*, vol. 65, no. 5, pp. 2220–2233, May 2017.