

Design of Water Distribution in Jangaon Town

K. Suresh kumar¹, Bolu kiran kumar²

Assistant Professor, Department of Civil Engineering, NNRESGI, Hyderabad, Telangana, India^{1,2}.

ABSTRACT

In India, water convenience controls people movement. To satisfy the building up the water enthusiasm for creating urban masses, it's awfully essential to supply the perfect aggregate through the effective style of pipe sort out. The head major errand for water utilities is to course water of the perfect mean individual customers with needed load through a scattering mastermind. The workplace in most Indian urban networks is simply out there for specific hours out of consistently, weight is sporadic, and besides the water is of crude quality. The perform of a course of action of channels is to make water at adequate weight and stream. Be that as it may, weight is lost by the movement of crushing at the pipe divider. The grouping of settled test conditions legitimize the pressure flow relationship and these are encased into framework showing PC code packs to encourage their answer and use. Thusly, while orchestrating an arrangement of pipe system, the main point is to attain adequate weight at offer motivation to get required proportion of water to the supporter. Misuse modernly out there PC code, the producer reacts streams and loads inside the framework and streams in and out to/from the tank for essential loadings. For this examination space, lodging board Zone of Jangoan town is known and moreover the framework show for the area into record is dealt with and thought about for pipe weight, speed, water age, etc.

The put in limit of the subject is 11.13(MLD) at any rate the rhythmic movement give of water to the agrarian homes punctually providing house affiliations is 7.10(MLD). The per capita give is 120(LPCD). The endeavor would cost concerning twenty.28crores similarly as mass water supply(treatment and transmission structure) administers by Telangana consumable give Corporation (TDWSC), Intra-town office system regulated by the Village water and Sanitation Committees All ebb and flow office plans and in progression potablecomes in nation and strong square measures are integrated to the TDSWC adventure.

KEY WORDS:Analysis, EPA net 2.0, other modes of usages, water distribution network

1.INTRODUCTION

Water bought to be considered as a limited asset that has breaking points and limits to its benefit and appropriateness to be utilized. Water is useful to masses in various classes. Business water use incorporates water for motels, lodgings, eateries, working environment structures, diverse business offices, and non military personnel and military foundations. Residential water use is maybe the first essential day by day utilization of water for many folks. The domestic use incorporates water that is used in the house every day, just as water for conventional house capacities, such as drinking, sustenance planning, washing, clothing articles of clothing and dishes, flushing washrooms, and watering yards and greenery enclosures. Industrial water use could be an important asset to the country's ventures for such capacities as procedure, cleaning, transportation, weakening, and cooling in producing facilities. The water dissemination organize should fulfill the need of overstated development of populace. To broaden the expectations for everyday comforts water conveyance water dispersion is required amid a noteworthy job. The office insufficiency is that the significant burden in topographical areasince the water dissemination framework is irregular framework. Underneath this topic water is circulated to the

inhabitants discontinuously for couple of hours amid seven days. These conditions make the water in pipelines inclined to cross tainting through waste item and polluted groundwater. So as thereto we will in general square measure giving nonstop water conveyance framework to give twenty four hours, day and night and one year to each house hold WHO square measure in completion of the system moreover while not falling into any negative weight. Discontinuous framework won't give water endlessly through system funnels, by this sullyng of channels contribution to exhaust territory and moreover bacterium arrangement happens. That defilements and bacterium development results hurtful impacts inside the customer wellbeing. To stay away from this consistent water framework has been planned amid this examination to maintain a strategic distance from negative weights and full length accommodate every hub constantly.

Changing scene for the usage of farming contains a pleasant outcome on the stream of water. Changes in scene by the expulsion of trees and soils changes the stream of water inside the local environment and also influences the cycle of water. Thus, a great deal ofwater is keep inside the dirt that edges farming. In any case, since farming is the human activity

that expends the freshest water, this can put an extreme strain on local crisp assets prompting the demolition of local biological communities.

Water appropriation frameworks fuses pipeline arranges and related components, a large portion of that is underground and presented to soil consumption and mechanical worry from the incorporating soil, surface traffic, and inside water weight [1]. Pipe disappointment in water conveyance frameworks upsets the office to clients and decreases the mindful ness of the framework. It's discovered that concerning thirty fifth to hour of the gave volume is squandered gratitude to pipe spillages [2]. Along these lines, investigation, the board and arranged support and restoration programs square measure important to legitimately work existing water dissemination frameworks [3].

II. STUDY AREA:

JANGAON municipal space for a projected population of 109045 in 2048 the desired water demand 16.930 MLD. We tend to have a previous out there information on the city in conducting a survey. The supply of facility is from Devadula carry Irrigation and also the filter is Chitakodur filter. The population

details as well as projections for the horizon years 2018, 2033, 2048 square measure calculated by exploitation population prediction ways. The project is split into nine zones supported the topography, proximity and case of property from numerous dependable and property sources. General Location of the knoll at the side of its elevation wherever it's potential to construct WTP/MBBR solely and also the distance in mts from the water grid pipeline up to the foot of the knoll.

The put in capability of the theme is 11.13(MLD) however the current provide of water to the agricultural habitations punctually providing house connections is 7.10(MLD). The per capita provide is 120(LPCD). The project would price concerning twenty.28crores as well as bulk water supply(treatment and transmission system) manages by Telangana potable provide Corporation (TDWSC), Intra-village facility system managed by the Village water and Sanitation Committees All existing facility schemes and in progress potablecomes in rural and concrete square measureas are integrated to the TDSWC project..

III. ABOUT EPANET

EPANET could be a worm that performs extended amount simulation of hydraulic and water quality Behaviour inside controlled pipe networks. A network consists of pipes, nodes (pipe junctions), pumps, valves and storage tanks or reservoirs. EPANET tracks the flow of water in every pipe, the pressure at every node, the peak of water in every tank, and also the concentration of a chemical species throughout the Network throughout a simulation amount comprised of multiple time steps. Additionally to chemical species, water age and supply tracing can even be simulated. EPANET is intended to be a look tool for rising our understanding of the movement and fate of potable constituents inside distribution systems. It contains a progressive hydraulic analysis engine that has the subsequent capabilities.

- It places no limit on the size of the network that can be analyzed.
- It computes friction head loss using the Hazen-William, Darcy-Weisbach or Chezy-Manning formula.
- Includes minor head losses for bends, fittings, etc.
- The model has constant or variable speed pumps.
- It computes pumping energy and cost.
- The model has various types of valves including shutoff, check, pressure regulating, and flow control valves.
- It allows storage tanks to have any shape (i.e., diameter can vary with height)
- It considers multiple demand categories at nodes, each with its own pattern of time variation
- Can perform system operation on both simple tank level and timer controls and on complex rule-based controls.


EPANET's Windows user interface provides a network editor that simplifies the process of building piping network models and editing their properties. Various data reporting and visualization tools such as graphical views,

Creating A Model: From toolbars selected reservoirs for sump, nodes for junction, pipes and tank and generated (TDWS) water supply scheme map. Also gave Hazen-William formula for head loss calculation and set default unit of flow as l/s.

Further following tasks were carried out:

- Values of elevations assigned to nodes and tank.
- Add pipe length and diameter.
- Values of total head assigned to reservoir and pump.
- Editing time pattern and pump curve.
- Run the network (If the run was unsuccessful than the status report window will appear indicating what the problem was. If it ran successfully you can view the computed results)
-

A1 COLOR
Revised ELBR location at WTP dt.10-2-16



(a)


(b)

Table – 1 Pipe results

S.no	Diameter of Pipe (mm)	Material	Length of the Pipe (m)
1	150		
2	200		
3	250	D.1	4540
4	300		
5	350		
6	400		
7	450		
8	500	D.1	10190
9	600		
10	700		
11	750		

(c)

Figure 1: (a) Map of the Study space, (b) Network design using EPANET, (c) Tables of provided pipe.



IV. POPULATION AND DEMAND ASSESSMENT

The populace was anticipated utilizing three techniques as appeared with formulae:

- Arithmetic Increase Method: $P_n = [P_0 + n \cdot x]$,

- Geometric Increase Method: $P_n = P_0[1 + r/100]^n$ and

- Incremental Increase Method: $P_n = P_0 + n \cdot \bar{x} + (n(n+1))/2 \cdot y$

Where, P_n = Prospective or anticipated populace after n decades from the present,

P_0 = Population at present,

n = No. of decades among now and future,

$\bar{x}$ = Average (number juggling mean) of populace increments in the known decades,

r = Assumed development rate (%),

y = Average of steady increment of the known decades.

The evaluated masses in Jangaon for the accompanying three decades using these methods close by water demand is aforethought in table three. The masses was foreseen up to the season of 2048. Also, for indistinct the water demand has been resolved. The people desire is apportioned from the projection of the season of 1991, 1981, 1991, and 2011 from the Census Department, Government of India. From the results dynamic Increase framework gave splendid course of action concerning the improvement of masses. The results for the more expanded term decade people square measure 2018 (60200), 2033 (81022), 2048 (109045).

V. CALCULATION OF PIPE DIAMETERS

When the structure release is known, pipe widths are accepted such that the speeds of stream in channels stay between 0.6 to 3 m/s. littler speed is expected for channels of littler measurement and bigger speed for funnels of bigger distance across. The loss of head in the channels is then determined utilizing Hazen Williams recipe (or monogram) as:

$$V = 0.849 \times C \times R \times 0.63S \times 0.54$$

Where: V = mean speed of stream in pipe (m/s)

R = pressure driven span (mean profundity) in m

S = pressure driven inclination

C = coefficient of unpleasantness of pipe

As far as width D of the pipe, the above equation lessens to:

$$V = 0.354 C \times D \times 0.63S \times 0.54$$

Where, D is the distance across of the pipe in meters. Communicated as far as head misfortune h_f and the length L of the pipe, the

Hazen Williams' recipe takes the accompanying structure:

$h_f = 6.843(D \times 1.167) \times V C \times 1.852$ The release Q (m³/s) is given by: $Q = 0.278 C$

$$\times D \times 2.63S \times 0.54$$

COMPREHENSIVE WATER SUPPLY SCH				
ZONE WISE WATER DEM				
Zone Nos.	Name of Zone	Zone area in Hecter	2018	
			Population	Den (M)
Zone - 1	WEAVER'S COLONY	153.35	4106	0.6
Zone - 2	GIRINIGADDA GODOWN	127.30	3631	0.5
Zone - 3	NEW ABADI COURT	209.88	7711	1.2
Zone - 4	OLD ABADI(E-SEVA)	30.21	6622	1.0
Zone - 5	GUNDLA GADDA	44.39	9624	1.5
Zone - 6	HAMALIGADDA	73.68	7076	1.1
Zone - 7	AMBEDKARNAGAR	10.87	1596	0.2
Zone - 8	Opp to RTC Bus Depot	281.15	13116	2.0
Zone - 9	HOUSIGN BOARD	689.97	6718	1.0
Total		1130.28	60200	9.3

(b)

Figure - 2: (a) Table of Population and Demand Assessment, (b) Table of Input data for design of distribution network

VI. CONCLUSION

In this paper attempt has been made to build up a Water Distribution System abuse EPANET PC code an instrument to help the evaluation of the pressure driven conduct of office dissemination arrange. The most focal point of this examination is to explore the water conveyance arrange and decide inadequacies (assuming any) in its appropriateness, execution and its utilization. At the tip of the investigation it had been discovered that the resultant weights at all the intersections and furthermore the streams with their speeds at all channels square measure sufficiently sufficient to supply water inside the examination space. It had been found out that the funnels associated with the tanks as conveyance channels to the contrary pipes have littler breadths. Correlation of those outcomes shows that the reenacted model seems to be genuinely close real system. Release should be misrepresented

to accomplish the base interest. This study would encourage the office engineers.

VII. REFERENCES

- [1]. Ahammed M, Melchers RE. Probabilistic analysis of underground pipelines subject to combined stresses and corrosion. EngStruct 1997; 19(12):988–94.
- [2]. Babovic, V., Dre' court, J., Keijzer, M. & Hansen, P. F. 2002 A data mining approach to modelling of water supply assets. Urban Wat. 4, 401–414.
- [3]. Sægrov, S., Melo Baptista, J. F., Conroy, P., Herz, R. K., LeGauffre, P., Moss, G., Oddevald, J. E., Rajani, B., and Schiatti, M., 1999. Rehabilitation of water networks: Survey of research needs and ongoing efforts. Urban Water, 1, 15–22.
- [4]. M. Prudhvikanth., S. Maanasa., and T. Naga Rupesh. (2013). "Design of Water Distribution Network by Using EPANET Software", ELK Asia Pacific Journals.
- [5]. Payal Lungariya., Namrata Katharotiy a., Darshan Mehta., and Sahita Waikhom (2016). "Analysis of Continuous Water Distribution in Surat City using EPANET: A Case Study", Global Research and Development Journal of Engineering,
- [6]. Zheng, Y Wu. "Method for optimizing design and rehabilitation of water distribution systems". Retrieved 2010-04-22 USA patent No. 7,593,839.